

System with Std Toggle/ link / no Sta-lok	System with Std Toggle/ link / Sta-lok	System with Long Toggle/Link / No Sta-lok	Boat Size	Wire Diameter	Pin Diameter	Rod Size	System Length
CF-500	N/A	N/A	16' - 24' (6.1 - 7.3m)	1/8", 5/32", 3/16" (3mm -5mm)	Up to 3/8" (5mm)	N/A	31'-1" (9.5m)
CF-700	N/A	N/A	24' - 28' (7.3 - 8.5m)	5/32" - 7/32" (4mm - 5.5mm)	Up to 7/16" (8mm)	N/A	38' (11.6m)
1100-44	1100-01	1100 & 1100-24	27'-31' (8.2 - 9.5m)	3/16" (5mm)	3/8" (9.5mm)	-4	43' (13m)
1100-55	1100-02	1100 & 1100-23	27'-31' (8.2 - 9.5m)	7/32" (5.5mm)	7/16" (11mm)	-6	43' (13m)
1100-66	1100-03	1100 & 1100-22	27'-31' (8.2 - 9.5m)	1/4" (6mm)	1/2" (13mm)	-8	43' (13m)
1100-66	1100-04	1100 & 1100-22	27'-31' (8.2 - 9.5m)	9/32" (7mm)	1/2" (13mm)	-10	43' (13m)
2100-44	2100-01	2100 & 2100-24	30'-42' (9.1 - 12.8m)	1/4" (6mm)	1/2" (13mm)	-8	49'-3" (15m)
2100-44	2100-02	2100 & 2100-24	30'-42' (9.1 - 12.8m)	9/32" (7mm)	1/2" (13mm)	-10	49'-3" (15m)
2100-55	2100-03	2100 & 2100-22	30'-42' (9.1 - 12.8m)	5/16" (8mm)	5/8" (16mm)	-12	49'-3" (15m)
2100-55	2100-04	2100 & 2100-22	30'-42' (9.1 - 12.8m)	3/8" (10mm)	5/8" (16mm)	-17	49'-3" (15m)
3100-44	3100-01	3100 & 3100-22	41'-55' (12.5 - 16.8m)	5/16" (8mm)	5/8" (16mm)	-12	64'-7-1/2" (19.7m)
3100-44	3100-02	3100 & 3100-22	41'-55' (12.5 - 16.8m)	3/8" (10mm)	5/8" (16mm)	-17	64'-7-1/2" (19.7m)
3100-55	3100-03	3100 & 3100-24	41'-55' (12.5 - 16.8m)	7/16" (11mm)	3/4" (19mm)	-22	64'-7-1/2" (19.7m)
3100-66	3100-04	3100 & 3100-28	41'-55' (12.5 - 16.8m)	1/2" (12.7mm)	7/8" (22mm)	-22	64'-7-1/2" (19.7m)
4100-44	4100-01	Custom Toggle/Link	54'-65' (16.5 - 19.8m)	7/16" (11mm)	3/4" (19mm)	-30	78'-9-1/4" (24m)
4100-55	4100-02	Custom Toggle/Link	54'-65' (16.5 - 19.8m)	1/2" (12.7mm)	7/8" (22mm)	-30	78'-9-1/4" (24m)

4100-55	4100-03	Custom Toggle/Link	54'-65' (16.5 - 19.8m)	9/16" (14.2mm)	7/8" (22mm)	-40	78'-9-1/4" (24m)
---------	---------	--------------------	------------------------	----------------	-------------	-----	------------------